## NSN 3020-00-945-4170



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-945-4170 **Body Style:** Plain, solid **Attachment Method:** Clamp Pitch Diameter: 0.6250 inches **Teeth Quantity:** 60 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Outside Diameter:** 0.646 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.281 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.187 inches both ends **Hub Style Designator:** Split first end **Hub Diameter:** 0.250 inches first end **Clamping Surface Length:** 0.241 inches first end **Precision Classification:** Quality number 10 **Special Features:** Anodized after all machining Material:

Aluminum alloy 2024

**Material Specification:** 

Qq-a-225/6, t4 federal specification single material response

**Surface Treatment:** 

Anodize

**Surface Treatment Specification:** 

Mil-a-8625, type 1 military specification single treatment response

## NSN 3020-00-945-4170

Spur Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
No Fiig:

Mil-std (military Standard):

Mil-a-8625 spec.