NSN 3020-00-945-5596

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-945-5596 **Body Style:** Webbed, offset, solid Pitch Diameter: 1.7917 inches **Teeth Quantity:** 43 **Bore Style:** 10a w/ keyway both ends Hardness Rating: 25.0 rockwell c hub and 35.0 rockwell c hub **Outside Diameter:** 1.913 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.376 inches first end **Body Recess Depth:** 0.160 inches second end **Face Width:** 0.250 inches **Bore Diameter:** 0.437 inches both ends **Keyway Width:** 0.097 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.272 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.625 inches first end Material: Steel comp 4340 or steel comp 4140 **Material Specification:** Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response **Style Designator:** Protruding hub, recessed body Shelf Life:

N/a

Unit Of Measure:

NSN 3020-00-945-5596

Spur Gear - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-s-5000 spec.