## NSN 3020-00-945-9379



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-945-9379 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.5417 inches **Teeth Quantity:** 65 **Bore Style:** W/counterbore both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.556 inches Nominallength: 0.261 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.200 inches first end **Face Width:** 0.062 inches **Bore Diameter:** 0.125 inches both ends

Counterbore Depth:
0.030 inches both ends
Counterbore Diameter:
0.300 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.312 inches first end
Precision Classification:
Quality number 10

## NSN 3020-00-945-9379

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-s-7720 spec.



Material:
Steel comp 303
Material Specification:
Mil-s-7720, comp 303s military specification single material response
Surface Treatment:
Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Δ27300