NSN 3020-00-946-2208

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-946-2208 **Attachment Method:** Clamp Pitch Diameter: 2.2500 inches **Teeth Quantity:** 144 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Outside Diameter:** 2.279 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.314 inches first end **Face Width:** 0.128 inches **Bore Diameter:** 0.187 inches both ends **Hub Style Designator:** Split first end **Hub Diameter:** 0.250 inches first end **Clamping Surface Length:** 0.205 inches first end **Precision Classification:** Quality number 11 Material: Aluminum alloy **Material Specification:** Qq-a-268, t4 federal specification single material response **Surface Treatment:** Anodize first gear **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Protruding hub Shelf Life:

N/a

NSN 3020-00-946-2208

Spur Antibacklash Gear - Page 2 of 2



Unit Of Mea	sure:
-------------	-------

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.