## NSN 3020-00-946-2222



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-946-2222 **Body Style:** Plain, solid **Pitch Diameter:** 0.5000 inches **Teeth Quantity:** 32 **Bore Style:** Plain both ends **Backlash Designation:** Grade b **Outside Diameter:** 0.531 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.188 inches first end **Face Width:** 0.062 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.281 inches first end **Precision Classification:** Quality number 11 Material: Steel comp 303 or aluminum alloy 2024 **Material Specification:** Mil-s-7720 military specification single material response or qq-a-268, t4 federal specification single material response **Surface Treatment:** Passivate or anodize **Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response or mil-a-8625, type 1 military specification single treatment response **Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 3020-00-946-2222

Spur Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.