NSN 3020-00-947-5299



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-947-5299 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.7333 inches **Teeth Quantity:** 88 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 plain transversely through hub, first end and 1 threaded transversely through hub, first end **Outside Diameter:** 0.750 inches Nominallength: 0.375 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.375 inches first end **Mounting Hole Diameter:**

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-225/6, t4 federal specification single material response

0.046 inches transversely through hub, first end

NSN 3020-00-947-5299

Spur Gear - Page 2 of 2



_	•		_			
ن	ırfa	\sim	Irο	o+n	20r	٠.
u	ai ia	uc.	116	аш	161	IL.

Anodize

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300