NSN 3020-00-947-6797



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-947-6797 **Thread Class:** 3b first end **Thread Direction:** Left-hand first end **Body Style:** Plain, with lightening holes **Attachment Method:** Mounting hole Pitch Diameter: 13.5000 inches **Teeth Quantity:** 135 **Bore Style:** Thread series designator partially threaded first end **Mounting Hole Thread Series Designator:** Unf axially through body, second end Thready Qty Per Inch (tpi): 10 first end **Thread Size:** 7.000 inches first end **Mounting Hole Thread Size:** 0.250 inches axially through hub, first end **Criticality Code Justification:** Feat **Mounting Hole Type And Quantity:** 16 threaded axially through body, second end **Outside Diameter:** 13.668 inches **Tooth Form:** Standard Distance Between Body Face And Protruding Hub End:

Pressure Angle: 20.0000 degrees 0.957 inches first end **Face Width:** 0.413 inches **Bore Diameter:** 7.035 inches second end **Thread Length:** 0.750 inches first end **Hub Style Designator:** Plain first end

NSN 3020-00-947-6797

Spur Gear - Page 2 of 2



Hub Diameter:
8.280 inches first end
Special Features:
Flight safety critical
Material:
Steel
Material Specification:
Ams 6260 assn standard single material response
Style Designator:
Protruding hub
Thread Series Designator:
Buttress first end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A27300