NSN 3020-00-948-0321

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-948-0321

Body Style: Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 1.2821 inches **Teeth Quantity:** 123 Bore Style: Plain both ends **Backlash Designation:** Grade c Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end Mounting Hole Thread Size: 0.112 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 1.2987 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.187 inches first end Face Width: 0.094 inches **Bore Diameter:** 0.188 inches both ends Hub Style Designator: Plain first end **Hub Diameter:** 0.370 inches first end **Precision Classification:** Quality number 10 Material: Aluminum alloy 6061 **Material Specification:**

Qq-a-225/8, t6 federal specification single material response

NSN 3020-00-948-0321

Spur Gear - Page 2 of 2



Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.