NSN 3020-00-948-9838

Groove Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-948-9838 **Counterbore Diameter:** 4.000 inches **Counterbore Depth:** 1.450 inches **Groove Depth:** 0.875 inches **Groove Width:** Between 0.312 inches and 0.875 inches **Outside Diameter:** 12.750 inches **Overall Length:** 4.250 inches **Keyway Width:** 0.500 inches **Bore Length:** 4.250 inches **Distance From Center Of Bore To Bottom Of Keyway:** 1.793 inches V Groove Angle In Deg: 34.0 Pitch Diameter: 12.6250 inches **Taper Bore Major Diameter:** 3.115 inches **Taper Bore Minor Diameter:** 2.770 inches **Material And Location:** Iron, cast **Face Width:** 2.188 inches **Design Form:** Plain **Bore Type:** Tapered Bearings: Not included **Taper Major Diameter Location:** Aa end **Groove Quantity:**

Counterbore Feature:
Included

NSN 3020-00-948-9838

Groove Pulley - Page 2 of 2



Counterbore Location:
Bb end
Keying Facility:
Included
Keying Facility Type:
Keyway
Split Hub Feature:
Not included
Lightening Hole:
Not included
Integral Cooling Vane:
Not included
Groove Shape:
V
Bore Feature:
Included
Protruding Hub Characteristic:
Plain
Hub End Outside Diameter And Location:
4.468 inches aa end and 6.135 inches bb end
Distance From Outside Flange/rim To Hub End And Location:
1.125 inches aa end and 0.939 inches bb end
First Step Face Largest Diameter And Location:
4.940 inches both ends
First Step Length And Location:
0.500 inches both ends
Second Step Length And Location:
0.625 inches both ends
Hub End Outside Diameter And Location:
4.468 inches both ends
Quantity:
1
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-a