## NSN 3020-00-949-1587

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-949-1587 Pitch Diameter: 1.2500 inches **Teeth Quantity:** 120 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Outside Diameter:** 1.2698 inches **Tooth Form:** Special **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.188 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.375 inches first end **Precision Classification:** Quality number 12 Material: Aluminum alloy 2024 or aluminum alloy 6061 **Material Specification:** Qq-a-268, alloy alclad, t4 federal specification 1st material response or qq-a-325, grade t6 federal specification 2nd material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Protruding hub Shelf Life: N/a

No

**Unit Of Measure:** 

**Demilitarization:** 

## NSN 3020-00-949-1587

Spur Antibacklash Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.