## NSN 3020-00-949-3617

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-949-3617

Outside Diameter:
Between 1.272 inches and 1.276 inches
Overall Length:
0.375 inches
Thread Size:
0.138-32
Bore Diameter:
Between 0.3150 inches and 0.3155 inches
Bore Length:
0.375 inches
Pitch Diameter:
Between 1.222 inches and 1.224 inches
Securing Hole Quantity:
1
Furnished Items And Quantity:
Nonesetscrew 1
Face Width:
0.125 inches
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Not included
Hole Location:
Located on hub portion between hub end and face
Keying Facility:
Not included
Securing Method:
Threaded hole
Lightening Hole:
Not included
Securing Location:
Aa end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:

26

## **NSN 3020-00-949-3617** Sprocket Wheel - Page 2 of 2



Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.148 inches
Hub End Outside Diameter And Location:
0.500 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.250 inches both ends
Material:
Steel, qq-s-764, type 303, cond a-canceled or steel, qq-s-764, type 303se, cond a-canceled
Material:
Steel comp 303 or steel comp 303se
Material Specification:
Qq-s-764, type 303, cond a-canceled federal specification 1st material response and qq-s-764, type 303se, cond a-canceled federal
specification 2nd material response
Surface Treatment:
Passivate
Style Designator:
Plain
Surface Treatment:
Passivated
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c