

View Online at <https://aerobasegroup.com/nsn/3020-00-949-5661>

**Body Style:**

Plain, solid

**Attachment Method:**

Mounting hole

**Pitch Diameter:**

Between 0.6240 inches and 0.6250 inches

**Teeth Quantity:**

60

**Bore Style:**

Plain both ends

**Backlash Designation:**

Grade c

**Mounting Hole Thread Series Designator:**

Unc transversely through hub, first end

**Mounting Hole Thread Qty Per Inch (tpi):**

40 transversely through hub, first end

**Mounting Hole Thread Size:**

0.112 inches transversely through hub, first end

**Mounting Hole Type And Quantity:**

1 threaded transversely through hub, first end

**Outside Diameter:**

0.644 inches

**Tooth Form:**

Standard

**Pressure Angle:**

20.0000 degrees

**Distance Between Body Face And Protruding Hub End:**

0.187 inches first end

**Face Width:**

0.125 inches

**Bore Diameter:**

0.188 inches both ends

**Hub Style Designator:**

Plain first end

**Hub Diameter:**

0.370 inches first end

**Precision Classification:**

Quality number 12

**Material:**

Aluminum alloy 2024 and aluminum alloy 6061

**Material Specification:**

Qq-a-225/6, t4 federal specification single material response and qq-a-225/8, t6 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 1 military specification single treatment response

**Style Designator:**

Protruding hub

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A27300

**Mil-std (military Standard):**

Mil-a-8625 spec.