NSN 3020-00-949-7178



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-949-7178 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.5277 inches **Teeth Quantity:** 19 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.583 inches Nominallength: 0.190 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.145 inches first end **Face Width:** 0.045 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.440 inches first end **Precision Classification:** Quality number 9 Material: Aluminum alloy 6061

Material Specification:

Qq-a-225/8, t6 federal specification single material response

NSN 3020-00-949-7178

Spur Gear - Page 2 of 2

Mil-c-5541 spec.



Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):