NSN 3020-00-950-9994

Flat Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-950-9994

| Counterbore Diameter: |
|--|
| 0.251 inches |
| Counterbore Depth: |
| 0.250 inches |
| Outside Diameter: |
| 1.375 inches |
| Overall Length: |
| 0.508 inches |
| Outside Diameter: |
| 1.375 inches |
| Thread Size: |
| 6-40 thd size |
| Bore Diameter: |
| 0.187 inches |
| Bore Length: |
| 0.508 inches |
| Flange Width: |
| 0.062 inches |
| Pitch Diameter: |
| 1.250 inches |
| Flange Quantity: |
| 2 |
| Securing Hole Quantity: |
| 3 |
| Material And Location: |
| Steel |
| Face Width: |
| 0.250 inches |
| Design Form: |
| Plain |
| Bore Type: |
| Straight |
| Bearings: |
| Not included |
| Counterbore Feature: |
| Included |
| Counterbore Location: |
| Aa end |
| Hole Location: |
| Two holes located 90 degrees apart on one end of hub, one hole located on tope of other end of hub |
| |
| Keying Facility: |

NSN 3020-00-950-9994 Flat Pulley - Page 2 of 2



| Securing Method: |
|--|
| Threaded hole |
| Split Hub Feature: |
| Not included |
| Lightening Hole: |
| Not included |
| Integral Cooling Vane: |
| Not included |
| Crown Face: |
| Not included |
| Rim Type: |
| Solid |
| Flange Location: |
| Outside |
| Bore Feature: |
| Included |
| Securing Location: |
| Aa end |
| Hub End Outside Diameter And Location: |
| 0.500 inches aa end and 0.374 inches bb end |
| Distance From Outside Flange/rim To Hub End And Location: |
| 0.218 inches aa end and 0.040 inches bb end |
| Style Designator: |
| Plain |
| Fsc Application Data: |
| 1. Radio sets, radio, except navigation and types, nonairborne |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T353-a |
| |