# NSN 3020-00-956-8942

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-956-8942

# Outside Diameter:

Between 0.711 inches and 0.715 inches

# **Overall Length:**

0.375 inches

## Thread Size:

0.138-32

# Bore Diameter:

0.250 inches

Bore Length:

0.375 inches

# Pitch Diameter:

Between 0.661 inches and 0.663 inches

# Securing Hole Quantity:

1

# Furnished Items And Quantity:

## Setscrew, one each

Face Width:

#### 0.125 inches

Design Form:

Plain

#### Bore Type:

Straight

#### Counterbore Feature:

Not included

#### Hole Location:

Centered 0.120 in.From end of hub

#### **Keying Facility:**

Not included

#### Securing Method:

Threaded hole

#### Lightening Hole:

Not included

#### Protruding Hub Characteristic:

Plain

#### Securing Location:

Aa end

#### Belt/chain/film Size For Which Designed:

Roller chain

#### Roller Chain Pitch Type For Which Designed:

Single pitch

#### **Teeth Row Quantity:**

1

# **NSN 3020-00-956-8942** Sprocket Wheel - Page 2 of 2



Teeth Quantity Per Row:
14
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.148 inches
Hub End Outside Diameter And Location:
0.500 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.250 inches aa end
Material:
Steel, qq-s-764, type 303-canceled
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303-canceled federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Plain
Surface Treatment:
Passivated
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T353-c