NSN 3020-00-959-5366

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-959-5366

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.8125 inches
Teeth Quantity:
39
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Mounting Hole Type And Quantity:
1 plain axially through body, first end
Outside Diameter:
0.854 inches
Nominallength:
0.312 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.218 inches first end
Face Width:
0.093 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.406 inches first end
Precision Classification:
Quality number 10 or quality number 11
Mounting Hole Diameter:
0.050 inches transversely through hub, first end
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:

Anodize

NSN 3020-00-959-5366

Spur Gear - Page 2 of 2



Surface Treatment	Specification:
-------------------	----------------

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.