NSN 3020-00-960-4116

Spur Gear - Page 1 of 2

Body Style: Plain, solid

Mounting hole

Pitch Diameter:

0.8125 inches

Attachment Method:



View Online at https://aerobasegroup.com/nsn/3020-00-960-4116

Teeth Quantity:
52
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 transversely through hub, first end
Mounting Hole Thread Size:
0.112 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
0.844 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.215 inches first end
Face Width:
0.175 inches
Bore Diameter:
0.183 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.406 inches first end
Precision Classification:
Quality number 10 or quality number 11
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a federal specification single material response

NSN 3020-00-960-4116

Spur Gear - Page 2 of 2



$\overline{}$			-			
<u>ن</u>	irto	2	Iro	atn	าคท	

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300