

View Online at <https://aerobasegroup.com/nsn/3020-00-962-1027>

Outside Diameter:

Between 0.664 inches and 0.668 inches

Overall Length:

Between 0.370 inches and 0.380 inches

Thread Size:

0.138-32

Bore Diameter:

Between 0.3145 inches and 0.3150 inches

Bore Length:

Between 0.370 inches and 0.375 inches

Pitch Diameter:

Between 0.614 inches and 0.616 inches

Securing Hole Quantity:

1

Furnished Items And Quantity:

Setscrew 1

Face Width:

Between 0.120 inches and 0.130 inches

Design Form:

Plain

Bore Type:

Straight

Counterbore Feature:

Not included

Hole Location:

Located on hub

Keying Facility:

Not included

Securing Method:

Threaded hole

Lightening Hole:

Not included

Protruding Hub Characteristic:

Plain

Securing Location:

Aa end

Belt/chain/film Size For Which Designed:

Roller chain

Roller Chain Pitch Type For Which Designed:

Single pitch

Teeth Row Quantity:

1

Teeth Quantity Per Row:

13

Hardness Rating Test Method:

Not rated

Bore Bearing:

Not included

Hub External Keyway:

Not included

Tooth Pitch:

0.1475 inches

Hub End Outside Diameter And Location:

0.445 inches both ends and 0.505 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.245 inches both ends and 0.255 inches both ends

Material:

Steel, mil-s-7720, comp 303s or steel, mil-s-7720, comp 303se

Material:

Steel comp 303 or steel comp 303se

Material Specification:

Mil-s-7720, comp 303s military specification 1st material response and mil-s-7720, comp 303se military specification 2nd material response

Surface Treatment:

Passivate

Style Designator:

Plain

Surface Treatment:

Passivated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T353-c

Mil-std (military Standard):

Mil-s-7720 spec.