NSN 3020-00-963-6665

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-963-6665

Rody Style:
Body Style: Plain, solid
Pitch Diameter:
Between 0.7490 inches and 0.7500 inches
Teeth Quantity:
72
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Outside Diameter:
0.769 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.187 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.250 inches first end
Precision Classification:
Quality number 10 or quality number 11
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Style Designator:
Protruding hub
Furnished Items And Quantity:
2 setscrew
Shelf Life:
N/a

NSN 3020-00-963-6665

Spur Gear - Page 2 of 2



		. ~				
ı	ını	t Of	· M	മമ	CII	re.

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.