NSN 3020-00-963-6708

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-963-6708 **Body Style:** Plain, solid **Pitch Diameter:** Between 0.8740 inches and 0.8750 inches **Teeth Quantity:** 84 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Outside Diameter:** 0.894 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.187 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.250 inches first end **Precision Classification:** Quality number 10 or quality number 11 Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t4 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Style Designator:** Protruding hub **Furnished Items And Quantity:** 2 setscrew

N/a

Shelf Life:

NSN 3020-00-963-6708

Spur Gear - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.