## NSN 3020-00-965-6236

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-965-6236 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.7190 inches **Teeth Quantity:** 110 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Thread Size:** 0.138 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 1.750 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.219 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.437 inches first end **Precision Classification:** Quality number 11 Material: Aluminum alloy 2024

**Material Specification:** 

Qq-a-225/6, t4 federal specification single material response

## NSN 3020-00-965-6236

Spur Gear - Page 2 of 2



$\overline{}$			-			
<b>~</b> I	ırfa	ഫ	ırc	natr	nΔn	

Anodize

**Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300