NSN 3020-00-965-6240



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-965-6240 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 2.1250 inches **Teeth Quantity:** 136 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Thread Size:** 0.138 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 2.125 inches Nominallength: 0.344 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.219 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.437 inches first end **Precision Classification:**

Quality number 10

Aluminum alloy 2024

Material:

NSN 3020-00-965-6240

Spur Gear - Page 2 of 2

Fiig: A27300



Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No