NSN 3020-00-966-8622

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-966-8622

Attachment Method:
Mounting hole
Pitch Diameter:
2.5000 inches
Teeth Quantity:
120
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 transversely through hub, first end
Hardness Rating:
75.0 rockwell b and 83.0 rockwell c
Mounting Hole Thread Size:
0.112 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 plain transversely through hub, first end and 1 threaded transversely through hub, first end
Outside Diameter:
2.5410 inches
Nominallength:
0.609 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.281 inches first end
Face Width:
0.104 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
Plain second end
Hub Diameter:
0.625 inches first end
Mounting Hole Diameter:
0.062 inches transversely through hub, first end
Material:
Steel comp 303s
Material Specification:

Mil-s-7720, comp 303s military specification single material response

NSN 3020-00-966-8622

Spur Antibacklash Gear - Page 2 of 2



Passivate
Style Designator:
Peripheral face, hubless
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-s-7720 spec.

Surface Treatment: