NSN 3020-00-968-4509

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-968-4509

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
3.2292 inches
Teeth Quantity:
155
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 transversely through hub, first end
Mounting Hole Thread Size:
0.138 inches transversely through hub between firstend flange and body
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
3.269 inches
Nominallength:
0.343 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.228 inches first end
Face Width:
0.115 inches
Bore Diameter:
0.187 inches both ends
Hub Diameter:
0.375 inches first end
Precision Classification:
Quality number 10 or quality number 11
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:

Anodize

NSN 3020-00-968-4509

Spur Gear - Page 2 of 2



Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:

Protruding hub

r roudding na

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.