## NSN 3020-00-969-8807

**Attachment Method:** 

Spur Antibacklash Gear - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3020-00-969-8807



Mounting hole Pitch Diameter: 1.5000 inches **Teeth Quantity:** 96 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 1.530 inches **Tooth Form:** Standard Pressure Angle: 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.234 inches first end **Face Width:** 0.114 inches **Bore Diameter:** 0.098 inches both ends **Hub Style Designator:** 1 step first end **End Length:** 0.156 inches first end **Precision Classification:** Quality number 12 **End Diameter:** 0.250 inches first end First Step Length: 0.073 inches first end First Step Diameter: 0.563 inches first end Material: Steel comp 303 hub **Material Specification:** Qq-s-763, cond a federal specification single material response hub

## NSN 3020-00-969-8807

Mil-std (military Standard):

Mil-a-8625 spec.

Spur Antibacklash Gear - Page 2 of 2



Surface Treatment:
Passivate hub
Surface Treatment Specification:
Ms171, finish no. 5.4.1 military standard single treatment response hub
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300