## NSN 3020-00-970-6527

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-970-6527 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.7500 inches **Teeth Quantity:** 84 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Mounting Hole Thread Series Designator:** Unc axially through body, first end **Mounting Hole Thread Size:** 0.138 inches axially through body, first end **Mounting Hole Type And Quantity:** 3 threaded axially through body, first end **Outside Diameter:** 1.792 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.500 inches first end **Precision Classification:** Quality number 10 or quality number 11 **Bolt Hole Circle Diameter:** 1.125 inches axially through body, first end

Material:

Steel comp 303s

**Material Specification:** 

Mil-s-7720 military specification single material response

## NSN 3020-00-970-6527

Spur Gear - Page 2 of 2



Surface Treatment:
Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-s-7720 spec.