## NSN 3020-00-971-5611

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-971-5611 **Attachment Method:** Clamp Pitch Diameter: 2.8750 inches **Teeth Quantity:** 184 **Bore Style:** Plain both ends **Outside Diameter:** 2.9062 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.313 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.187 inches both ends **Hub Style Designator:** Split first end **Hub Diameter:** 0.250 inches first end **Clamping Surface Length:** 0.250 inches first end Material: Stainless steel spring **Material Specification:** Qq-a-225/6 federal specification single material response second gear **Surface Treatment:** Passivate hub **Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response hub **Style Designator:** Protruding hub Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

## NSN 3020-00-971-5611

Spur Antibacklash Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.