## NSN 3020-00-971-9669

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-971-9669

Body Style:
Webbed, offset, with lightening holes
Attachment Method:
Mounting hole
End Application:
Apn147
Pitch Diameter:
1.8750 inches
Teeth Quantity:
180
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 plain transversely through hub, first end and 1 threaded transversely through hub, first end
Outside Diameter:
1.896 inches
Nominallength:
0.250 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.125 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.375 inches first end
Mounting Hole Diameter:
0.029 inches transversely through hub, first end
Material:

Aluminum alloy 2024

## NSN 3020-00-971-9669

Spur Gear - Page 2 of 2

A27300

Mil-a-8625 spec.

Mil-std (military Standard):



## Material Specification: Qq-a-250/4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Protruding hub, recessed body Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fiig: