## NSN 3020-00-975-9620

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-975-9620

**Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.8906 inches **Teeth Quantity:** 57 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Mounting Hole Type And Quantity:** 2 plain axially through body, first end **Outside Diameter:** 0.922 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees Face Width: 0.187 inches **Bore Diameter:** 0.188 inches both ends **Precision Classification:** Quality number 10 or quality number 11 **Mounting Hole Diameter:** 0.125 inches axially through body, first end **Bolt Hole Circle Diameter:** 0.500 inches axially through body, first end Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t4 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** 

Hubless

Shelf Life:

N/a

## NSN 3020-00-975-9620

Spur Gear - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.