NSN 3020-00-976-3567

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-976-3567

| 3 |
|--|
| Body Style: |
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 1.4091 inches |
| Teeth Quantity: |
| 31 |
| Bore Style: |
| Tapered second end |
| Hardness Rating: |
| 45.0 rockwell c and 50.0 rockwell c |
| Mounting Hole Type And Quantity: |
| 1 countersunk transversely through hub, first end |
| Outside Diameter: |
| 1.484 inches |
| Nominallength: |
| 0.347 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 22.5000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.135 inches second end |
| Face Width: |
| 0.225 inches |
| Taper Major Diameter: |
| 0.594 inches first end |
| Counterbore Depth: |
| 0.070 inches second end |
| Counterbore Diameter: |
| 0.594 inches second end |
| Hub Style Designator: |
| Plain both ends |
| Hub Diameter: |
| 0.960 inches first end |
| Mounting Hole Diameter: |
| 0.069 inches transversely through hub, first end |
| Material: |
| Steel |

Material Specification:

Ams5616 assn standard single material response

NSN 3020-00-976-3567

Spur Gear - Page 2 of 2



| Surface Treatmer |
|------------------|
|------------------|

Passivate

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300