## NSN 3020-00-976-5316



Spur Gear Sector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-976-5316 **Attachment Method:** Mounting hole **Teeth Quantity:** 72 **Bore Style:** W/counterbore counterbore, first end Pitch Radius: 3.0000 inches **Mounting Hole Thread Series Designator:** Unc axially through body, first end Hardness Rating: 20.0 rockwell c and 36.0 rockwell c **Mounting Hole Thread Size:** 0.138 inches axially through body, first end and 0.172 inches axially through body, first end **Mounting Hole Type And Quantity:** 4 threaded axially through body, first end and 5 plain axially through body, first end and 10 threaded axially through body, first end and 2 plain axially through body, first end and 1 plain axially through body, first end **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Face Width:** 0.560 inches **Bore Diameter:** 2.000 inches counterbore, first end **Counterbore Depth:** 2.512 inches counterbore, first end **Counterbore Diameter:** 0.137 inches counterbore, first end **Outside Radius:** 3.043 inches **Precision Classification:** Quality number 10 or quality number 11 Arc Length: 9.425 inches **Mounting Hole Diameter:** 0.189 inches axially through body, first end and 0.135 inches axially through body, first end Material: Stainless steel

N/a

Hubless Shelf Life:

**Style Designator:** 

## NSN 3020-00-976-5316

Spur Gear Sector - Page 2 of 2



| ш | ın | 10 | <i>(</i> )+ | Measure: |  |
|---|----|----|-------------|----------|--|
|   |    |    |             |          |  |

--

Demilitarization:

No

Fiig:

A27300