NSN 3020-00-984-5348

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-984-5348

Body Style:
Webbed, offset, solid
Attachment Method:
Mounting hole
Pitch Diameter:
2.0833 inches
Teeth Quantity:
100
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Mounting Hole Type And Quantity:
2 plain axially through body, first end
Outside Diameter:
2.125 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Face Width:
0.093 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.250 inches first end
Precision Classification:
Quality number 10 or quality number 11
Mounting Hole Diameter:
0.156 inches axially through body, first end
Bolt Hole Circle Diameter:
0.500 inches axially through body, first end
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response

NSN 3020-00-984-5348

Spur Gear - Page 2 of 2



Style Designator:
Flush hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Demilitarization: No

Mil-std (military Standard):

Mil-a-8625 spec.