## NSN 3020-00-984-8332

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-984-8332

Outside Diameter:
1.182 inches
Overall Length:
0.268 inches
Keyway Width:
Any acceptable
Bore Diameter:
0.343 inches
Bore Length:
0.268 inches
Distance From Center Of Bore To Bottom Of Keyway:
Any acceptable
Pitch Diameter:
0.932 inches
Face Width:
0.125 inches
Guide:
Not included
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Not included
Keying Facility:
Included
Keying Facility Type:
Keyway
Securing Method:
Press fit
Lightening Hole:
Not included
Protruding Hub Characteristic:
Stepped
Groove/step Location:
An and

Aa end

Belt/chain/film Size For Which Designed:

Roller chain

**Securing Location:** 

**Roller Chain Pitch Type For Which Designed:** 

Single pitch

## **NSN 3020-00-984-8332** Sprocket Wheel - Page 2 of 2



Teeth Row Quantity:
1
Teeth Quantity Per Row:
24
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.148 inches
First Step Face Largest Diameter And Location:
0.750 inches both ends
First Step Length And Location:
0.060 inches both ends
Second Step Length And Location:
0.083 inches both ends
Material:
Steel, qq-s-763, class 303, cond a
Material:
Steel comp 303
Material Specification:
Qq-s-763, class 303, cond a federal specification single material response
Quantity:
1
Surface Treatment:
Passivate
Style Designator:
Plain
Surface Treatment:
Passivated
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c