## NSN 3020-00-986-8394

Sprocket Wheel - Page 1 of 2

**Outside Diameter:** 

1.257 inches



View Online at https://aerobasegroup.com/nsn/3020-00-986-8394

Overall Length:
0.887 inches
Outside Diameter:
1.505 inches
Bore Diameter:
0.250 inches
Bore Length:
0.887 inches
Pitch Diameter:
1.273 inches
Furnished Items And Quantity:
Setscrew, two each
Face Width:
0.563 inches
Guide:
Included
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Oddiner bore i catare.
Not included
Not included
Not included  Guide Type:
Not included  Guide Type:  Sprocket side flange
Not included  Guide Type:  Sprocket side flange  Keying Facility:
Not included  Guide Type:  Sprocket side flange  Keying Facility:  Not included
Not included  Guide Type:  Sprocket side flange  Keying Facility:  Not included  Securing Method:
Not included  Guide Type: Sprocket side flange  Keying Facility: Not included  Securing Method: Setscrew
Not included  Guide Type: Sprocket side flange  Keying Facility: Not included  Securing Method: Setscrew  Lightening Hole:
Not included  Guide Type: Sprocket side flange  Keying Facility: Not included  Securing Method: Setscrew  Lightening Hole: Not included
Not included  Guide Type: Sprocket side flange  Keying Facility: Not included  Securing Method: Setscrew  Lightening Hole: Not included  Protruding Hub Characteristic:
Not included  Guide Type: Sprocket side flange  Keying Facility: Not included  Securing Method: Setscrew  Lightening Hole: Not included  Protruding Hub Characteristic: Plain
Not included  Guide Type: Sprocket side flange  Keying Facility: Not included  Securing Method: Setscrew  Lightening Hole: Not included  Protruding Hub Characteristic: Plain  Securing Location:
Not included  Guide Type: Sprocket side flange  Keying Facility: Not included  Securing Method: Setscrew  Lightening Hole: Not included  Protruding Hub Characteristic: Plain  Securing Location: Aa end
Not included  Guide Type: Sprocket side flange  Keying Facility: Not included  Securing Method: Setscrew  Lightening Hole: Not included  Protruding Hub Characteristic: Plain  Securing Location: Aa end  Belt/chain/film Size For Which Designed:
Not included  Guide Type: Sprocket side flange  Keying Facility: Not included  Securing Method: Setscrew  Lightening Hole: Not included  Protruding Hub Characteristic: Plain  Securing Location: Aa end  Belt/chain/film Size For Which Designed: Positive drive belt
Not included  Guide Type: Sprocket side flange  Keying Facility: Not included  Securing Method: Setscrew  Lightening Hole: Not included  Protruding Hub Characteristic: Plain  Securing Location: Aa end  Belt/chain/film Size For Which Designed: Positive drive belt  Teeth Row Quantity:

## **NSN 3020-00-986-8394** Sprocket Wheel - Page 2 of 2



Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.200 inches
<b>Hub End Outside Diameter And Location:</b>
0.928 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.324 inches aa end
Material:
Steel
Material:
Steel
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c