## NSN 3020-00-987-1271

Sprocket Wheel - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3020-00-987-1271



## Outside Diameter:

1.761 inches

## Bore Diameter:

0.250 inches

### Bore Length:

Between 0.500 inches and 0.505 inches

#### Pitch Diameter:

1.783 inches

#### Face Width:

Between 0.500 inches and 0.505 inches

#### Guide:

Not included

#### **Design Form:**

Webbed

#### Bore Type:

Straight

## Counterbore Feature:

Not included

#### Lubrication Mode:

Visible means

#### **Keying Facility:**

Not included

#### Lightening Hole:

Not included

#### Belt/chain/film Size For Which Designed:

Positive drive belt

#### **Teeth Row Quantity:**

1

#### Teeth Quantity Per Row:

28

## Hardness Rating Test Method:

Not rated

## **Bore Bearing:**

Included

## Tooth Pitch:

0.200 inches

## Hub End Outside Diameter And Location:

1.000 inches both ends

## Material:

Aluminum alloy, qq-a-268, t0

## Material:

Aluminum alloy, qq-a-268, t0

# NSN 3020-00-987-1271

Sprocket Wheel - Page 2 of 2

Surface Treatment:

Anodize

Style Designator:

Webbed or spoked

Surface Treatment:

Anodize per mil-a-8625, type 2, class 1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

Т353-с

