# NSN 3020-00-988-6910

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-988-6910

#### **Body Style:**

Plain, solid

#### **Pitch Diameter:**

1.6250 inches

# Teeth Quantity:

78

# Bore Style:

Plain both ends

#### Backlash Designation:

Grade c

### **Outside Diameter:**

1.667 inches

#### Nominallength:

0.312 inches

#### **Tooth Form:**

Standard

# Pressure Angle:

20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

0.212 inches first end

# Face Width:

0.100 inches

#### Bore Diameter:

0.188 inches both ends

#### Hub Style Designator:

Plain first end

#### Hub Diameter:

0.375 inches first end

#### **Precision Classification:**

Quality number 10 or quality number 11

#### **Special Features:**

Block, stop rivetted to body

#### Material:

Aluminum alloy 2024

#### **Material Specification:**

Qq-a-225/6, t4 federal specification single material response

# Surface Treatment:

Anodize

#### **Surface Treatment Specification:**

Mil-a-8625, type 1 military specification single treatment response

#### Style Designator:

Protruding hub

# NSN 3020-00-988-6910

Spur Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

# Mil-std (military Standard):

Mil-a-8625 spec.

