NSN 3020-00-991-3395

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-991-3395

| Body Style: |
|--|
| Webbed, offset, solid |
| Pitch Diameter: |
| 1.2500 inches |
| Teeth Quantity: |
| 60 |
| Bore Style: |
| Plain both ends |
| Backlash Designation: |
| Grade c |
| Outside Diameter: |
| 1.270 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.031 inches first end |
| Face Width: |
| 0.324 inches |
| Bore Diameter: |
| 0.187 inches both ends |
| Hub Style Designator: |
| Plain both ends |
| Hub Diameter: |
| 0.438 inches second end |
| Precision Classification: |
| Quality number 10 or quality number 11 |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Qq-s-763, class 303, cond a federal specification single material response |
| Surface Treatment: |
| Passivate |
| Style Designator: |
| Protruding hubs |
| Furnished Items And Quantity: |
| 1 lubricant impregnated bearing |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 3020-00-991-3395

Spur Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300