

View Online at <https://aerobasegroup.com/nsn/3020-00-992-1206>

**Groove Depth:**

0.800 inches

**Groove Width:**

Between 0.375 inches and 0.656 inches

**Outside Diameter:**

4.150 inches

**Overall Length:**

1.688 inches

**Keyway Width:**

0.188 inches

**Thread Size:**

0.312-18

**Bore Diameter:**

0.625 inches

**Bore Length:**

1.688 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

0.406 inches

**V Groove Angle In Deg:**

38.0

**Pitch Diameter:**

Between 2.700 inches and 4.100 inches

**Securing Hole Quantity:**

1

**Furnished Items And Quantity:**

Setscrew 1

**Material And Location:**

Iron, cast

**Face Width:**

Between 0.720 inches and 1.085 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

1

**Counterbore Feature:**

Not included

**Hole Location:**

Centered 0.219 in.From end of hub

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Securing Method:**

Threaded hole

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Not offset

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Bore Feature:**

Included

**Protruding Hub Characteristic:**

Plain

**Securing Location:**

Aa end

**Hub End Outside Diameter And Location:**

1.750 inches aa end and 1.545 inches bb end

**Distance From Outside Flange/rim To Hub End And Location:**

0.415 inches aa end and 0.780 inches aa end and 0.188 inches bb end

**Special Features:**

Variable pitch for 3l, 4l, 5l v-belts

**Quantity:**

1

**Surface Treatment:**

Paint

**Style Designator:**

Webbed or spoked

**Surface Treatment:**

Painted

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-a