

View Online at <https://aerobasegroup.com/nsn/3020-00-992-1207>

**Groove Depth:**

Between 0.781 inches and 1.000 inches

**Groove Width:**

Between 0.500 inches and 0.875 inches

**Outside Diameter:**

3.150 inches

**Overall Length:**

1.688 inches

**Keyway Width:**

0.188 inches

**Thread Size:**

0.312-18

**Bore Diameter:**

0.625 inches

**Bore Length:**

1.688 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

0.406 inches

**V Groove Angle In Deg:**

36.0

**Pitch Diameter:**

Between 1.700 inches and 3.200 inches

**Securing Hole Quantity:**

1

**Furnished Items And Quantity:**

Setscrew, one each

**Material And Location:**

Iron, cast

**Face Width:**

Between 0.625 inches and 1.000 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

1

**Counterbore Feature:**

Not included

**Hole Location:**

Centered 0.219 in.From face of hub, top of keyway

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Securing Method:**

Threaded hole

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Not offset

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Standard V-belt Section Designation For Which Designed:**

3bl-4l-5l

**Bore Feature:**

Included

**Protruding Hub Characteristic:**

Plain

**Securing Location:**

Bb end

**Hub End Outside Diameter And Location:**

1.688 inches aa end and 1.500 inches bb end

**Distance From Outside Flange/rim To Hub End And Location:**

0.438 inches aa end and 0.250 inches bb end

**Quantity:**

1

**Surface Treatment:**

Paint

**Style Designator:**

Webbed or spoked

**Surface Treatment:**

Painted

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-a