NSN 3020-00-992-5717



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-992-5717 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 2.3958 inches **Teeth Quantity:** 115 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Mounting Hole Thread Series Designator:** Unc axially through body, first end Mounting Hole Thready Qty Per Inch (tpi): 32 axially through body, first end **Mounting Hole Thread Size:** 0.138 inches axially through body, first end **Mounting Hole Type And Quantity:** 1 plain transversely through hub, first end and 1 threaded transversely through hub, first end **Outside Diameter:** 2.4374 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** 1 step first end **End Length:** 0.188 inches first end **Precision Classification:** Quality number 10 **End Diameter:**

First Step Length:

0.500 inches first end

0.0625 inches first end

NSN 3020-00-992-5717 Spur Gear - Page 2 of 2



First Step Diameter:
0.875 inches first end
Mounting Hole Diameter:
0.086 inches axially through body, first end
Special Features:
Mtg holes 90 degrees apart
Material:
Aluminum alloy 2024 body
Material Specification:
Qq-a-225/6, t4 federal specification single material response teeth
Surface Treatment:
Passivate hub
Style Designator:
Protruding hub
Furnished Items And Quantity:
1 setscrew
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300