## NSN 3020-00-995-5254



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-995-5254 **Body Style:** Webbed, solid **Spline Quantity:** 12 second end Pitch Diameter: 2.2381 inches **Teeth Quantity:** 36 **Bore Style:** Partial first end **Spline Pitch Diameter:** 0.6000 inches second end **Hardness Rating:** 91.0 rockwell superficial 15-n and 94.5 rockwell superficial 15-n **Outside Diameter:** 2.355 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 1.545 inches second end **Face Width:** 0.390 inches **Bore Diameter:** 0.750 inches first end **Bore Depth:** 0.600 inches first end **Hub Style Designator:** 1 step second end **End Length:** 0.855 inches second end **End Diameter:** 0.940 inches second end First Step Length:

0.690 inches second endFirst Step Diameter:0.984 inches second end

**Special Features:** 

Hub end is threaded 0.9375-20 unef-3a, 0.470 in.Lg

Material:

Steel uns k24065

## NSN 3020-00-995-5254

Spur Gear - Page 2 of 2

**Fiig:** A27300



## Material Specification: Ams 6471 assn standard single material response Surface Treatment: Oxide Surface Treatment Specification: Ams 2485 assn standard single treatment response Style Designator: Protruding hub Shelf Life: N/a Unit Of Measure: --Demilitarization: No