# NSN 3020-00-995-5254

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-995-5254

# Body Style:

Webbed, solid

Spline Quantity:

12 second end

## Pitch Diameter:

2.2381 inches

# **Teeth Quantity:**

36

Bore Style:

Partial first end

## Spline Pitch Diameter:

0.6000 inches second end

### Hardness Rating:

91.0 rockwell superficial 15-n and 94.5 rockwell superficial 15-n

### Outside Diameter:

2.355 inches

## Tooth Form:

Standard

## Pressure Angle:

20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

1.545 inches second end

## Face Width:

0.390 inches

## Bore Diameter:

0.750 inches first end

#### Bore Depth:

0.600 inches first end

## Hub Style Designator:

1 step second end

#### End Length:

0.855 inches second end

#### End Diameter:

0.940 inches second end

#### First Step Length:

0.690 inches second end

## First Step Diameter:

0.984 inches second end

#### **Special Features:**

Hub end is threaded 0.9375-20 unef-3a, 0.470 in.Lg

# Material:

Steel uns k24065

# NSN 3020-00-995-5254

Spur Gear - Page 2 of 2



Material Specification: Ams 6471 assn standard single material response Surface Treatment: Oxide Surface Treatment Specification: Ams 2485 assn standard single treatment response Style Designator: Protruding hub Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A27300