

View Online at <https://aerobasegroup.com/nsn/3020-00-997-0275>

**Attachment Method:**

Mounting hole

**Bore Style:**

Plain both ends

**Design Type:**

Spur all gears

**Backlash Designation:**

Grade c all gears

**Construction:**

Solid

**Outside Diameter:**

0.406 inches second gear

**Nominallength:**

0.562 inches

**Hub Length:**

0.250 inches between first and second gear

**Bore Diameter:**

0.187 inches both ends

**Hub Style Designator:**

Plain between first and second gear

**Hub Diameter:**

0.315 inches between first and second gear

**Precision Classification:**

Quality number 11 all gears or quality number 12 all gears

**Material:**

Steel comp 302 or steel comp 303 or steel comp 303se

**Material Specification:**

Qq-s-763, cond a federal specification 1st material response or qq-s-764, cond a federal specification 2nd material response or qq-s-764, cond a federal specification 3rd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072, finish e300 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A270a0

**Mil-std (military Standard):**

Mil-f-14072 spec.