NSN 3020-01-003-5023



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-003-5023 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.3430 inches and 0.3437 inches **Teeth Quantity:** 22 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.374 inches Nominallength: 0.343 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.218 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.187 inches both ends **Hub Style Designator:** Pinned first end

Hub Diameter: 0.375 inches first end **Precision Classification:** Quality number 12 Material: Steel comp 303 **Material Specification:** Aisi 303 assn standard single material response

NSN 3020-01-003-5023

Spur Gear - Page 2 of 2



_	•		_			
ن	ırfa	\sim	Irο	o+n	20r	٠.
u	ai ia	uc.	116	аш	161	IL.

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300