## NSN 3020-01-005-7900

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-005-7900

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 2.5000 inches **Teeth Quantity:** 60 **Bore Style:** 10b w/ 2 keyways both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 18 transversely through hub, first end Mounting Hole Thread Size: 0.313 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 2.583 inches Nominallength: 0.625 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.375 inches first end Face Width: 0.250 inches **Bore Diameter:** 0.610 inches both ends **Keyway Width:** 0.125 inches both ends Distance From Bore Center To Keyway Bottom: 0.430 inches both ends Hub Style Designator: Plain first end Hub Diameter: 1.250 inches first end Material: Steel

# NSN 3020-01-005-7900

Spur Gear - Page 2 of 2

### Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A27300

