NSN 3020-01-006-1302

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-006-1302

Attachment Method:

Clamp

Pitch Diameter:

Between 2.4990 inches and 2.5000 inches

Teeth Quantity:

160

Bore Style:

Plain both ends

Outside Diameter:

2.530 inches

Nominallength:

0.438 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.313 inches first end

Face Width:

0.125 inches

Bore Diameter:

0.250 inches both ends

Hub Style Designator:

Split first end

Hub Diameter:

0.313 inches first end

Clamping Surface Length:

0.250 inches first end

Precision Classification:

Quality number 10 or quality number 11

Special Features:

0.563 in. Diameter by 0.063 in. Lg second step on a end

Material:

Steel comp 303 hub

Material Specification:

Qq-s-764 federal specification single material response hub

Surface Treatment:

Passivate hub

Surface Treatment Specification:

Mil-f-14072 military specification single treatment response hub

Style Designator:

Protruding hub

NSN 3020-01-006-1302

Spur Antibacklash Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.

