NSN 3020-01-006-4789

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-006-4789

Attachment Method:
Mounting hole
Teeth Quantity:
37
Bore Style:
Plain both ends
Pitch Radius:
1.6666 inches
Backlash Designation:
Grade b
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thread Size:
0.164 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.2000 inches first end
Face Width:
0.120 inches
Bore Diameter:
0.375 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
1.3200 inches first end
Outside Radius:
1.1875 inches
Precision Classification:
Quality number 10
Arc Length:
2.4871 inches
Special Features:
One unthd hole 0.125 in. Diameter through hub parallel to bore, in line 60 degrees from end tooth
Material:
Steel comp 303
Material Specification:

Qq-s-764, type 303 cond a federal specification single material response

NSN 3020-01-006-4789

Spur Gear Sector - Page 2 of 2

Mil-f-14072 spec.



Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, finish e300 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):