NSN 3020-01-006-5268

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-006-5268

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.3750 inches
Teeth Quantity:
36
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unf transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
72 transversely through hub, first end
Mounting Hole Thread Size:
0.073 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 plain transversely through hub, first end and 1 threaded transversely through hub, first end
Outside Diameter:
0.396 inches
Nominallength:
0.202 inches
Tooth Form:
Standard
Glandard
Pressure Angle:
Pressure Angle:
Pressure Angle: 20.0000 degrees
Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End:
Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.125 inches first end
Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.125 inches first end Face Width:
Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.125 inches first end Face Width: 0.0770 inches
Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.125 inches first end Face Width: 0.0770 inches Bore Diameter:
Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.125 inches first end Face Width: 0.0770 inches Bore Diameter: 0.125 inches both ends
Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.125 inches first end Face Width: 0.0770 inches Bore Diameter: 0.125 inches both ends Hub Style Designator:
Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.125 inches first end Face Width: 0.0770 inches Bore Diameter: 0.125 inches both ends Hub Style Designator: Pinned first end
Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.125 inches first end Face Width: 0.0770 inches Bore Diameter: 0.125 inches both ends Hub Style Designator: Pinned first end Hub Diameter:
Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.125 inches first end Face Width: 0.0770 inches Bore Diameter: 0.125 inches both ends Hub Style Designator: Pinned first end Hub Diameter: 0.312 inches first end
Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.125 inches first end Face Width: 0.0770 inches Bore Diameter: 0.125 inches both ends Hub Style Designator: Pinned first end Hub Diameter: 0.312 inches first end Mounting Hole Diameter:

Material Specification:

Mil-s-7720, comp 303s, cond a military specification single material response

NSN 3020-01-006-5268

Spur Gear - Page 2 of 2



Surface Treatment:
Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-s-7720 spec.