## NSN 3020-01-007-5465

Helical Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-007-5465

Body Style:
Plain, solid
Pitch Diameter:
1.7676 inches
Teeth Quantity:
60
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Criticality Code Justification:
Feat
Outside Diameter:
1.809 inches
Teeth Type:
Single helix
Tooth Form:
Standard
Tooth Direction:
Left
Pressure Angle:
•
20.0000 degrees
20.0000 degrees
20.0000 degrees Helix Angle:
20.0000 degrees  Helix Angle: 45.0000 degrees
20.0000 degrees  Helix Angle: 45.0000 degrees  Distance Between Body Face And Protruding Hub End:
20.0000 degrees  Helix Angle: 45.0000 degrees  Distance Between Body Face And Protruding Hub End: 0.250 inches first end
20.0000 degrees  Helix Angle: 45.0000 degrees  Distance Between Body Face And Protruding Hub End: 0.250 inches first end  Face Width:
20.0000 degrees  Helix Angle: 45.0000 degrees  Distance Between Body Face And Protruding Hub End: 0.250 inches first end  Face Width: 0.187 inches
20.0000 degrees  Helix Angle: 45.0000 degrees  Distance Between Body Face And Protruding Hub End: 0.250 inches first end  Face Width: 0.187 inches  Bore Diameter:
20.0000 degrees  Helix Angle: 45.0000 degrees  Distance Between Body Face And Protruding Hub End: 0.250 inches first end  Face Width: 0.187 inches  Bore Diameter: 0.250 inches both ends
20.0000 degrees  Helix Angle: 45.0000 degrees  Distance Between Body Face And Protruding Hub End: 0.250 inches first end  Face Width: 0.187 inches  Bore Diameter: 0.250 inches both ends  Hub Style Designator:
20.0000 degrees  Helix Angle: 45.0000 degrees  Distance Between Body Face And Protruding Hub End: 0.250 inches first end  Face Width: 0.187 inches  Bore Diameter: 0.250 inches both ends  Hub Style Designator:  Pinned first end
20.0000 degrees  Helix Angle:  45.0000 degrees  Distance Between Body Face And Protruding Hub End:  0.250 inches first end  Face Width:  0.187 inches  Bore Diameter:  0.250 inches both ends  Hub Style Designator:  Pinned first end  Hub Diameter:
20.0000 degrees  Helix Angle: 45.0000 degrees  Distance Between Body Face And Protruding Hub End: 0.250 inches first end  Face Width: 0.187 inches  Bore Diameter: 0.250 inches both ends  Hub Style Designator: Pinned first end  Hub Diameter: 0.500 inches first end
20.0000 degrees  Helix Angle:  45.0000 degrees  Distance Between Body Face And Protruding Hub End:  0.250 inches first end  Face Width:  0.187 inches  Bore Diameter:  0.250 inches both ends  Hub Style Designator:  Pinned first end  Hub Diameter:  0.500 inches first end  Precision Classification:
20.0000 degrees  Helix Angle:  45.0000 degrees  Distance Between Body Face And Protruding Hub End:  0.250 inches first end  Face Width:  0.187 inches  Bore Diameter:  0.250 inches both ends  Hub Style Designator:  Pinned first end  Hub Diameter:  0.500 inches first end  Precision Classification:  Quality number 10
20.0000 degrees  Helix Angle: 45.0000 degrees  Distance Between Body Face And Protruding Hub End: 0.250 inches first end  Face Width: 0.187 inches  Bore Diameter: 0.250 inches both ends  Hub Style Designator: Pinned first end  Hub Diameter: 0.500 inches first end  Precision Classification: Quality number 10  Special Features:
Helix Angle: 45.0000 degrees  Distance Between Body Face And Protruding Hub End: 0.250 inches first end Face Width: 0.187 inches Bore Diameter: 0.250 inches both ends Hub Style Designator: Pinned first end Hub Diameter: 0.500 inches first end Precision Classification: Quality number 10 Special Features: Mtg holes 90 degrees apart; weapon system essential

Material Specification:

Qq-s-764 federal specification single material response sleeve

## NSN 3020-01-007-5465

Helical Gear - Page 2 of 2



Style Designator:
Protruding hub
Furnished Items And Quantity:
1 setscrew
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-m-20693 spec.