# NSN 3020-01-008-1326

Spur Gear - Page 1 of 2



# **Body Style:**

Plain, solid

### **Attachment Method:**

Clamp

# **End Application:**

Grumman aerospace corporation a10 aircraft

### **Pitch Diameter:**

1.2517 inches

# **Teeth Quantity:**

90

#### Bore Style:

Plain both ends

## **Outside Diameter:**

1.279 inches

## Nominallength:

0.211 inches

# Tooth Form:

Standard

## \_ .

Pressure Angle:

# 20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

0.015 inches second end

# Face Width:

0.071 inches

### **Bore Diameter:**

0.090 inches both ends

#### Hub Style Designator:

Split second end

### Hub Diameter:

0.380 inches second end

#### **Clamping Surface Length:**

0.140 inches first end

### Material:

Steel comp 303

# **Material Specification:**

Qq-s-764, type 303, cond a federal specification single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Mil-std-171, finish no. 5.4.1 military standard single treatment response

# Style Designator:

Protruding hubs



# NSN 3020-01-008-1326

Spur Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

# Mil-std (military Standard):

Mil-std-171 spec.

